Ordered HTML List

An ordered list starts with the `<ol>` tag. Each list item starts with the `<li>` tag.

The list items will be marked with numbers by default. Notwithstanding the list item marker can be changed using the `type` attribute. The type attribute can take the following values: "1", "A", "a", "I", or "i".

For example:

```
<h3>My Hobbies</h3>
<ol type="i">
  <li>Reading</li>
  <li>Laughing</li>
  <li>Programming</li>
</ol>
```

By default, an ordered list will start counting from 1, A, a, I, or i, based on the `type` selected. This can be controlled using the `start` attribute. The start attribute takes *numeric* value only.

For example:

```
<h3>My Hobbies</h3>
<ol type="a" start="10">
  <li>Reading</li>
  <li>Laughing</li>
  <li>Programming</li>
</ol>
```

List can be nested also.

For example:

```
<h3>My Hobbies</h3>
<ol>
  <li>
     Reading:
     <ul style="list-style-type: disc">
       <li>Mathematics</li>
       <li>Marketing</li>
     </ul>
  </li>
  <li>Laughing</li>
  <li>Programming</li>
</ol>
```

Click to Ask Question(s)



MR YOUNG

IGWURUTA | ISIOKPO | ELELE | IKIRI | OMOKU

mryoung.presmaltra.com.ng